Maryland Historical Trust

Maryland Inventory of Historic Properties number:

Reviewer, NR Program: Peter E. Kurtze

The bridge referenced herein was inventor Historic Bridge Inventory, and SHA provious The Trust accepted the Historic Bridge Inventoric Br	ded the Trust with	h eligibility	detern	ninatio	ns in	Februa	ary 200	01.
Eligibility Recommended X D C	LAND HISTOR			ot Rec	comm	ended		_
Criteria:ABCD C Comments:	onsiderations:	_AB	c_	_D _	_E_	_F_	_G	None
Peviewer OPS: Anne F Bruder			Date	s. 3	Anril 1	2001		

Date:__3 April 2001

MARYLAND INVENTORY OF HISTORIC BRIDGES HISTORIC BRIDGE INVENTORY MARYLAND STATE HIGHWAY ADMINISTRATION/MARYLAND HISTORICAL TRUST

MHT No. B-4613

SHA Bridge No. BC 3212 Bridge name MD 147 over Herring Run (Herring Run Bridge)
LOCATION: Street/Road name and number [facility carried] Harford Road (MD 147)
City/town Baltimore Vicinity
County Baltimore
This bridge projects over: Road Railway WaterX Land
Ownership: State County Municipal X Other
HISTORIC STATUS: Is the bridge located within a designated historic district? Yes NoX National Register-listed district National Register-determined-eligible district Locally-designated district Other
Name of district
BRIDGE TYPE: Timber Bridge: Beam Bridge: Truss -Covered Trestle Timber-And-Concrete
Stone Arch Bridge
Metal Truss Bridge
Movable Bridge: Swing Bascule Single Leaf Bascule Multiple Leaf Vertical Lift Retractile Pontoon
Metal Girder : Rolled Girder: Rolled Girder Concrete Encased Plate Girder: Plate Girder Concrete Encased
Metal Suspension
Metal Arch
Metal Cantilever
Concrete X: Concrete Arch X Concrete Slab Concrete Beam Rigid Frame
Other Type Name

B-4613

DESCRIPTION: Setting: Urban X Small town Rural
Describe Setting:
Bridge BC 3212 carries Harford Road (MD 147) over Herring Run in Baltimore City. Harford Road (MD 147) runs north-south and Herring Run flows west to east. The bridge is located within the Herring Run Park in the City of Baltimore.
Describe Superstructure and Substructure:
Bridge BC 3212 is a 3-span, 4-lane, closed spandrel concrete barrel arch bridge. The bridge was built in 1911, and was widened in 1927. The structure is 75.6 meters (248 feet) long and has a clear roadway width of 13.4 meters (44 feet); there are two sidewalks each measuring 2 meters (6.5 feet) wide. The out-to-out width is 18.2 meters (60 feet). The superstructure consists of three arches which support a concrete deck and concrete parapets. Arch spans #1 and #3 each have a span length of 17.7 meters (58 feet), while the center span has a length of 38.4 meters (126 feet). The bridge has a clear height of 8.2 meters (26.8 feet) over a Herring Run Park service road. The structure has concrete closed ornamental parapets. The substructure consists of two concrete abutments, two concrete piers and four concrete wingwalls. A plaque states that the bridge was built by the State Roads Commission in 1911. The bridge has a sufficiency rating of 44.2.
According to the 1995 inspection report, this structure was in fair condition with cracking, spalling and scaling. The asphalt wearing surface is cracked and the parapets have cracking with heavy scaling and efflorescence. The bottom of the arches are typically in poor condition with large cracks and efflorescence. Pier 1 has delaminated concrete on its west face. The wingwalls have light to moderate scaling and spalling with exposed reinforcement.
Discuss Major Alterations:
According to the 1995 Bridge Inspection Report, the structure was constructed in 1911 and was widened in 1927.
HISTORY:
WHEN was the bridge built: 1911, 1927 This date is: Actual X Estimated Source of date: Plaque X Design plans City/County bridge files/inspection form X

WHY was the bridge built?

Other (specify): _

Harford Road (MD 147) was established by the end of the eighteenth century and may follow the route of an earlier trail. The road was never as heavily traveled as the nearby Bel Air Road (U.S. 1). In 1908, the State Roads Commission, established under Governor Crothers, began a seven-year project that created a statewide road network through improvement of existing roads. Harford Road was one of those designated for improvement, and was paved and graded within Baltimore City and

B-4613

within Baltimore County from the city line north for a length of three miles. Timber bridges along Harford Road were also replaced at this time.

WHO was the designer?

State Roads Commission

WHO was the builder?

State Roads Commission

WHY was the bridge altered?

The bridge was widened to allow for increased traffic across the bridge.

Was this bridge built as part of an organized bridge-building campaign?

Yes, this bridge was built as part of the building and widening of Harford Road.

SURVEYOR/HISTORIAN ANALYSIS:

This bridge may have	National	Register significance	e for its	s association	with:
A - Events	X	B- Person		_	
C- Engineerin	g/archited	tural character	X	_	

The bridge is eligible for the National Register of Historic Places under Criteria A and C, as a significant example of concrete arch construction. The bridge was originally built by the State Roads Commission as part of the improvements to Harford Road, and was later widened under those same efforts. The structure has a high degree of integrity and retains such character-defining elements of the type as solid paneled concrete parapets, spandrel walls, arch barrel and ring, abutments, piers, and wingwalls.

Was the bridge constructed in response to significant events in Maryland or local history?

The advent of modern concrete technology fostered a renaissance of arch bridge construction in the United States. Reinforced concrete allowed the arch bridge to be constructed with much more ease than ever before and maintained the load-bearing capabilities of the form. As the structural advantages of reinforced concrete became apparent, the heavy, filled barrel of the arch was lightened into ribs. Spandrel walls were opened, to give a lighter appearance and to decrease dead load. This enabled the concrete arch to become flatter and multi-centered, with longer spans possible. Designers were no longer limited to the semicircular or segmental arch form of the stone arch bridge. The versatility of reinforced concrete permitted development of a variety of economical bridges for use on roads crossing small streams and rivers.

Maryland's roads and bridge improvement programs mirrored economic cycles. The first road improvement of the State Roads Commission was a 7 year program, starting with the Commission's establishment in 1908 and ending in 1915. Due to World War I, the period from 1916-1920 was one of relative inactivity; only roads of first priority were built. Truck traffic resulting from war related factories and military installations generated new, heavy traffic unanticipated by the builders of the early road system. From 1920-1929, numerous highway improvements occurred in response to the

increase in Maryland motor vehicles from 103,000 in 1920 to 320,000 in 1929, with emphasis on the secondary system of feeder roads which moved traffic from the primary roads built before World War I. After World War I, Maryland's bridge system also was appraised as too narrow and structurally inadequate for the increasing traffic, with plans for an expanded bridge program to be handled by the Bridge Division, set up in 1920. In 1920 under Chapter 508 of the Acts of 1920 the State issued a bond of \$3,000,000.00 for road construction; the primary purpose of these monies was to meet the state obligations involving the construction of rural post roads. The secondary purpose of these monies was to fund (with an equal sum from the counties) the building of lateral roads. The number of hard surfaced roads on the state system grew from 2000 in 1920 to 3200 in 1930. By 1930, Maryland's primary system had been inadequate to the huge freight trucks and volume of passenger cars in use, with major improvements occurring in the late 1930's.

As the nation's automotive traffic increased in the early twentieth century, local road networks were consolidated, and state highway departments were formed to supervise the construction and improvement of state roads. With a diverse topographical domain encompassing numerous small and large crossings, Maryland engineers quickly recognized the need for expedient design and construction through the standardization of bridge designs.

The concept and practice of standardization was one of the most important developments in engineering of the twentieth century. In Maryland, as in the rest of the nation, the standardized concrete types became the predominant bridge types built. In the period 1911 to 1920 (the decade in which standardized plans were introduced), beams and slabs constituted 65 percent and arches 35 percent of the extant 29 bridges built in Maryland during this period. In the following decade, 1921-1930, the beam (now the T-beam) and slab increased to 73 percent and the arch had declined to 27 percent of the 129 extant bridges; in the next decade (1931-1940), the beam and slab achieved 82 percent and arches had further declined, constituting only 18 percent of the total of extant bridges built on state-owned roads between 1931 and 1946.

Although beam and slab bridges became the utilitarian choice, it appears that the arch was selected when aesthetic as well as other site conditions were considered. The architectural treatment of extant arch bridges supports this assessment. Many of these bridges were multiple span structures with open spandrels or masonry facing. Another decorative feature of the concrete arch bridge was an open, balustrade-style parapet. Despite the popularity of ornamental arches and the increase in use of beam and slab bridges, examples of simpler, single and multiple span closed concrete arch bridges with solid parapets continued to be constructed throughout the early twentieth century.

Harford Road (MD 147) was established by the end of the eighteenth century and may follow the route of an earlier trail. The road was never as heavily traveled as the nearby Bel Air Road (U.S. 1). In 1908, the State Roads Commission, established under Governor Crothers, began a seven-year project that created a statewide road network through improvement of existing roads. Harford Road was one of those designated for improvement, and was paved and graded within Baltimore City and within Baltimore County from the city line north for a length of three miles. Timber bridges along Harford Road were also replaced at this time.

When the bridge was built and/or given a major alteration, did it have a significant impact on the growth and development of the area?

There is no evidence that the construction of this bridge had a significant impact on the growth and development of this area.

B-4613

Is the bridge located in an area which may be eligible for historic designation and would the bridge add to or detract from the historic/visual character of the potential district?

The bridge is located in an area which does not appear to be eligible for historic designation.

Is the bridge a significant example of its type?

The bridge is a good example of the State Roads Commission's early concrete arches which was later widened.

Does the bridge retain integrity of important elements described in Context Addendum?

The bridge retains the character-defining elements of its type, as defined by the Statewide Historic Bridge Context, including solid panel concrete parapets, spandrel walls, arch barrel and ring, abutments, piers, and wingwalls, however some deterioration is evident.

Is the bridge a significant example of the work of a manufacturer, designer, and/or engineer?

This bridge is a significant example of the work of the State Roads Commission in the 1910s and 1920s.

Should the bridge be given further study before an evaluation of its significance is made?

No further study of this bridge is required to evaluate its significance.

BIBLIOGRAPHY:

City/County inspection/bridge files	X	SHA inspection/bridge files
Other (list):		

Johnson, Arthur Newhall

The Present Condition of Maryland Highways. In Report on the Highways of Maryland. Maryland Geological Survey, The Johns Hopkins University Press, Baltimore.

P.A.C. Spero & Company and Louis Berger & Associates

1995 Historic Highway Bridges in Maryland: 1631-1960: Historic Context Report. Maryland State Highway Administration, Maryland State Department of Transportation, Baltimore, Maryland.

State Roads Commission


1958 A History of Road Building in Maryland. Published by author, Baltimore.

Tyrrell, H. Grattan


1909 Concrete Bridges and Culverts for Both Railroads and Highways. The Myron C. Clark Publishing Company, Chicago and New York.


SURVEYOR:

Date bridge recorded _	December 1997	
Name of surveyor Wal	lace, Montgomery & Associates / P.A.C. Spero & Company	
	A.C. Spero & Co., 40 W. Chesapeake Avenue, Baltimore, MD 21	204
Phone number(410) 296	5-1635 FAX number (410) 296-1670	NVE



B-4613 Herring Run Bridge, Bridge 3212 Harford Road (MD 147) over Herring Run Baltimore City Baltimore East Quad







County/State	HARFORD ROOVER HERRING RUN BALTIMURE CITY/MD STOGRAPHER TIM SCHUEN
Name of Pho	otographer IIM SCHUEN
Date 19	5
Location of	Negative SHR
Description	SOUTH APPROACH
Number 3	of 34.5

Inventory # <u>B-4613</u>



		MORE CITY/MD
Name of Pho	tographer	TIM SUHDEN
Date9	5	
Location of I		
Description	WEST	ELEVATION
: 		



County/State	BALTI	TIM SCH	2 HERRING RYI I MD UEN
Date 10	5		
Location of	Negative	SHA	€
Description	EAST	ELEVATION)
Number 33	of 36.5	•	

Inventory # <u>B-4613</u>



County/State	HARFORD RD WER HERRING R BALTIMORE CITY MO	_
Date 1/9	otographer TIM SCHOEN	
Location of 1	Negative SHA	
Description	NORTH APPROACH	
	of365	

Inventory # <u>B-4413</u>

HERRING RUN BRIDGE. JULT BY THE STATE RUADS COMMISSION 1914

County/State	B	ALT	IMOY	RE (LITY		
Name of Phot	ogr	aphei	r <u> </u>	im	SCHUE	N	
Date 19	5	_					
Location of N	lega	tive	SHI	4			
	0	0		0	212071	- 10	25
Description 3	W	PUP	QUE	(0)	MONTH	ENU	VF
	W	EST	PA	RAPE	TI		
~		-	_				
Number 35	. 7	فاسا	,				

Inventory # <u>B-4613</u>